










VÁLVULAS ROTATIVAS + ACTUADORES

ACTUADORES	Actuadores, serie	ARA600						90				ARC300	
													
Tensión de suministro													
24 VCA, 3 puntos		●		●	●	●		●	●	●		●	
24 VCA, 3 puntos, Conmutador auxiliar				●	●			●					
24 VCA, 2 puntos												●	
24 V CA/CC, Proporcional				●					●			●	
230 VCA, 3 puntos		●		●	●	●	●	●	●	●		●	
230 VCA, 3 puntos, Conmutador auxiliar		●		●	●	●	●	●	●				
230 VCA, 2 puntos		●	●	●			●	●				●	
230 VCA, 2 puntos, Conmutador auxiliar		●	●	●									
Tiempo de funcionamiento [s]		15	30	45	60	120	240	15	60	120	240	390	150
Par de torsión [Nm]		3	6	6	6	6	6	5	15	15	15	15	30




3 VÍAS VÁLVULA

PN [bar]	T [°C]	Serie	DN	Kvs [m³/h]																
6	-10 ... +110		20	12																
			25	18																
			32	28	●	●	●	●	●		●	●	●	●					●	
			40	44																
			50	60																
			65	90																
			80	150																
			100	225										●	●	●	●			●
125	280																			
150	400																			
10	-10 ... +110		25	10	●	●	●	●	●	●	●	●	●	●						
10	-10 ... +110		15	0,4 - 4																
			20	2,5 - 6,3	●	●	●	●	●	●	●	1)	1)	1)	1)	1)				
			25	6,3 - 10																
			32	16																
			40	25	●	●	●	●	●	●	●	1)	1)	1)	1)	1)				
50	40																			
10	-10 ... +110		20	6,3																
			25	10	●	●	●	●	●	●	●	1)	1)	1)	1)	1)				
			32	16																
			40	30	●	●	●	●	●	●	●	1)	1)	1)	1)	1)				
50	40																			
10	-10 ... +110		20	13/8																
			25	17/10	●	●	●	●	●	●	●	1)	1)	1)	1)	1)				
			32	32/20																
			40	45/30	●	●	●	●	●	●	●	1)	1)	1)	1)	1)				
			50	65/40																
10	-10 ... +110		20	2,5 - 6,3	●	●	●	●	●	●	●	1)	1)	1)	1)	1)				


● Recomendado ● Alternativa secundaria

1) Es necesario un kit de adaptador adicional

VÁLVULAS ROTATIVAS + ACTUADORES

ACTUADORES	Actuadores, serie	ARA600						90				ARC300										
																						
Tensión de suministro																						
24 VCA, 3 puntos			●		●	●	●		●	●	●			●								
24 VCA, 3 puntos, Conmutador auxiliar					●	●			●													
24 VCA, 2 puntos														●								
24 V CA/CC, Proporcional				●						●				●								
230 VCA, 3 puntos			●		●	●	●	●	●	●	●			●								
230 VCA, 3 puntos, Conmutador auxiliar			●		●	●	●	●	●	●	●											
230 VCA, 2 puntos		●	●		●				●	●				●								
230 VCA, 2 puntos, Conmutador auxiliar		●	●		●																	
Tiempo de funcionamiento [s]		15	30	45	60	120	240	15	60	120	240	390	150									
Par de torsión [Nm]		3	6	6	6	6	6	5	15	15	15	15	30									

4 VÍAS VÁLVULA

PN [bar]	T [°C]	Serie	DN	Kvs [m³/h]																	
6	-10 ... +110	4F 		40	44																
				50	60	●	●	●	●	●									●		
				65	90																
				80	150																●
				100	225																
6	-10 ... +110	T 		20	8	●	●	●	●	●	●	●	●	●	●	●	●				
10	-10 ... +110	4HG 		25	8 - 10	●	●	●	●	●	●	●	●	●	●	●	●				
10	-10 ... +110	VRG140 		15	2,5																
				20	4 - 6,3	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
				25	10																
				32	16																
				40	25			●	●	●	●	●	●	●	●	●	●	●	●	●	
50	40			●	●	●	●	●	●	●	●	●	●	●	●	●					
10	-10 ... +110	VRB140 		15	2,5																
				20	4 - 6,3	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
				25	10																
				32	16																
				40	30			●	●	●	●	●	●	●	●	●	●	●	●	●	
50	40			●	●	●	●	●	●	●	●	●	●	●	●	●					
10	-10 ... +110	VRB240 		20	4	●	●	●	●	●	●	●	●	●	●	●	●				

● Recomendado ● Alternativa secundaria

1) Es necesario un kit de adaptador adicional