







- Typisk användning
- Valfri användning
- Utökad användning

Produkt	Kvs	Tryckfall Δp [kPa]			ΔT [K]	Effekt [kW]*																								
		Typisk	Valfri	Utökad		6	8	10	12	14	16	18	20	22	25	30	35	40	45	50	55	60	65	70	75	80				
 Shuntventil och ställdon VRG130 + ARA600 	DN20	6,3	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN25	10	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN32	16	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN40	25	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN50	40	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
 Växlingsventil och ställdon VRG230 + ARA600 	DN20	6,3	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN25	10	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN32	16	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN40	30	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN50	40	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
 Shuntventil och ställdon VRG330 + ARA600 	DN20	13	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN25	17	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN32	32	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN40	45	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						
	DN50	65	5	10	15	5	6	7																						
						5	6	7																						
						5	6	7																						

* Effektrekommendation är relaterad till differentialtemperatur (ΔT) i typiska värmepumpsystem.