










VRIDANDE VENTILER + STÄLLDON

STÄLLDON	Ställdon serie	ARA600					90				ARC300		
Spänning													
24 VAC, 3-punkt		●		●	●	●		●	●	●		●	
24 VAC, 3-punkt, Extrabrytare				●	●			●					
24 VAC, 2-punkt												●	
24 V AC/DC, Proportionell				●					●			●	
230 VAC, 3-punkt		●		●	●	●	●	●	●	●		●	
230 VAC, 3-punkt, Extrabrytare		●		●	●	●	●	●	●				
230 VAC, 2-punkt		●	●	●			●	●				●	
230 VAC, 2-punkt, Extrabrytare		●	●	●									
Gångtid [s]		15	30	45	60	120	240	15	60	120	240	390	150
Vridmoment [Nm]		3	6	6	6	6	6	5	15	15	15	15	30




3-VÄGS VENTIL

PN [bar]	T [°C]	Serie	DN	Kvs [m³/h]																		
6	-10 ... +110		20	12																		
			25	18																		
			32	28	●	●	●	●	●		●	●	●	●						●		
			40	44																		
			50	60																		
			65	90																		
			80	150																		
			100	225																		
			125	280																		
			150	400																		
10	-10 ... +110		25	10	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
10	-10 ... +110		15	0,4 - 4																		
			20	2,5 - 6,3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
			25	6,3 - 10																		
			32	16																		
			40	25	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
			50	40																		
10	-10 ... +110		20	6,3																		
			25	10	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
			32	16																		
			40	30	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
			50	40																		
10	-10 ... +110		20	13/8																		
			25	17/10	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
			32	32/20																		
			40	45/30																		
			50	65/40	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
10	-10 ... +110		20	2,5 - 6,3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		













● Rekommenderad ● Sekundärt alternativ

1) Adeptsats behövs

VRIDANDE VENTILER + STÄLLDON

STÄLLDON	Ställdon serie	ARA600					90				ARC300		
													
Spänning													
24 VAC, 3-punkt		●		●	●	●		●	●	●		●	
24 VAC, 3-punkt, Extrabrytare				●	●			●					
24 VAC, 2-punkt												●	
24 V AC/DC, Proportionell				●						●		●	
					●								
230 VAC, 3-punkt		●		●	●	●	●	●	●	●		●	
230 VAC, 3-punkt, Extrabrytare		●		●	●	●	●	●	●				
230 VAC, 2-punkt		●	●	●			●	●				●	
230 VAC, 2-punkt, Extrabrytare		●	●	●									
Gångtid [s]		15	30	45	60	120	240	15	60	120	240	390	150
Vridmoment [Nm]		3	6	6	6	6	6	5	15	15	15	15	30

4-VÄGS VENTIL

PN [bar]	T [°C]	Serie	DN	Kvs [m³/h]															
6	-10 +110			40	44												●		
				50	60		●	●	●	●	●								
				65	90														
				80	150														
				100	225														
6	-10 +110			20	8	●	●	●	●	●	●	●	●	●	●	●			
10	-10 +110			25	8 - 10	●	●	●	●	●	●	●	●	●	●	●			
10	-10 +110			15	2,5														
				20	4 - 6,3	●	●	●	●	●	●	●	●	●	●	●	●	●	
				25	10														
				32	16														
				40	25														
50	40																		
10	-10 +110			15	2,5														
				20	4 - 6,3	●	●	●	●	●	●	●	●	●	●	●	●	●	
				25	10														
				32	16														
				40	30														
50	40																		
10	-10 +110			20	4	●	●	●	●	●	●	●	●	●	●	●			

● Rekommenderad

● Sekundärt alternativ

1) Adaptersats behövs